

# DMN960Y 990 Series Resettable Manual Call Point, Yellow, Complete With Back Box

#### General

The DMN960Y is a surface mount, YELLOW addressable 990 Series manual call point with a high strength plastic housing. The LED indicator provides visual confirmation of alarm initiation. The test key (included with each unit) facilitates functional testing of the call point. The manual call point is delivered complete with resetable element.

#### **Operating Principles**

The address of each call point is set at the commissioning stage by means of a seven-segment DIL switch. The device features plug and play terminal connections. A single alarm LED is provided on the call point and is controlled, independently of the call point, by the fire panel.

#### Accessories

It is possible to surface or flush mount any of the call points in the range. Optional accessories to accommodate this are available separately.

#### **Approvals**

All relevant manual call points in the range have been tested by LPC and approved by LPCB and a number of other approval authorities.



#### **Details**

- Addressable manual call point
- · LED alarm indicator
- Tamper resistant break glass design
- · Easy to test with self reset
- Fast response
- Plug and play terminal connections for fast wiring
- Allow wiring continuity testing before fitting
- Resettable element fitted

## DMN960Y 990 Series Resettable Manual Call Point, Yellow, Complete With Back Box

### **Technical specifications**

Physical dimensions	87 x 87 x 52 mm
Net weight	180 g
Colour	Yellow
Colour	YELLOW
Material	Polycarbonate / ABS
Dimensions (surface mount)	87 x 87 x 52 mm
Weight	180 g
Environmental	
Operating temperature	-20 to +60°C
Storage temperature	-30 to +80°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor
IP rating	IP53
Operating temperature (no icing)	-20°C to +60°C
Storage temperature	-30°C to +80°C
Relative humidity (no condensation)	0-95 %
IP Rating	IP53
Power supply	
DC Supply	17 - 28 VDC
Communications	5 to 9 V
Current consumpti	on
Quiescent/Alarm	350 μΑ
Switch on surge (4s)	750 μΑ
LED on	4 mA
Alarm indication	
	Red LED



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit ie.firesecurityproducts.com online or contact your sales representative.