

# II952ND

## Apollo Switch Monitor Unit - DIN Rail Mount (SA4700-300)

### General

---

II952ND is the new DIN-Rail switch monitor unit designed to monitor the state of one or more single pole, volt-free contacts connected on a single pair of cables to report the status. It has a selectable status reporting delay making it suitable for monitoring flow switches.

### Ease of Installation

---

Improved design for ease of wiring meaning faster installation – unit can be fitted to back-box before wiring is connected. Colour coded terminal blocks for easier identification (green for loop wiring, yellow for mains wiring, grey for inputs and low voltage relays).



### Details

---

- Improved design for ease of wiring meaning faster installation
- Loop powered
- Supervise one or more single pole, volt-free contacts connected on a single pair of cables
- Local LEDs signalling I/O and fault conditions
- Isolators within each device

# I1952ND

## Apollo Switch Monitor Unit - DIN Rail Mount (SA4700-300)

### Technical specifications

---

#### Electrical

---

Operating voltage	17 to 35 VDC
Protocol voltage	5-13V peak to peak

---

#### Physical

---

Physical dimensions	102 x 33 x 33 mm
Net weight	46 g

---

#### Environmental

---

Operating temperature	-40 to +70°C
Relative humidity	0 to 95% noncondensing
Environment	Indoor

---

#### Regulatory

---

Certification	CPR, EN54-17, EN54-18
---------------	-----------------------

---

#### Current consumption

---

Power-up surge	0.9 mA
Quiescent	0.5 mA
LEDs disabled (max.)	0.5 mA
Alarm (LEDs On) (max.)	2 mA

---



As a company of innovation, Carrier Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit [ie.firesecurityproducts.com](http://ie.firesecurityproducts.com) online or contact your sales representative.

Last updated on 27 April 2023 - 14:57