

CDXconventional CCP-W

Conventional Weatherproof Manual Call Point

Features

- ▶ Approved to EN54-11:2001
- ▶ Terminals can accommodate up to a 2.5 mm² solid conductor
- ▶ Other colours available on request
- ▶ Ingress Protection rated to IP67
- ▶ Approved by LPCB.

Description

The CCP-W is a Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals.

The unit can support either a 'Frangible Glass' element or a 'Non Frangible Plastic' element and features a weatherproof Housing to IP67, which means

it can be mounted in the most severe environmental conditions without water ingress.

IMPORTANT NOTE: After changing the element from Glass to Flexi, please confirm the operation by pressing the resettable element.



Specification

Ordering codes	CCP-W			
Nominal operating resistance	470 Ω			
Maximum contact resistance	200 Ω			
IP rating	IP67			
Operating / Storage temperature range	- 25 °C to + 70 °C			
Maximum humidity	95% RH - Non-condensing (at 40 °C)			
Colour / Case material	Red / ABS			
Weight (g) / Dimensions (mm)	234 / W 98 x H 94 x D 78			
Accessories	Frangible element	KAC / G / HE	Non-frangible element	KAC / EWS / HE